

Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

SECTION: 1. Product and company identification

1.1. Product identifier

Product form : Substance
Substance name : Ethane
CAS-No. : 74-84-0
Formula : C₂H₆

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use; Use as directed.

1.3. Details of the supplier of the safety data sheet

Praxair, Inc.
10 Riverview Drive
Danbury, CT 06810-6268 - USA
T 1-800-772-9247 (1-800-PRAXAIR) - F 1-716-879-2146
www.praxair.com

1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week
— Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887
(collect calls accepted, Contract 17729)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS US classification

Simple asphyxiant SIAS
Flam. Gas 1 H220
Press. Gas (Liq.) H280
Aquatic Acute 3 H402

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS02

GHS04

Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H220 - EXTREMELY FLAMMABLE GAS
H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION.
CGA-HG04 - MAY FORM EXPLOSIVE MIXTURES WITH AIR
CGA-HG01 - MAY CAUSE FROSTBITE.

Precautionary statements (GHS US) :

P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Heat, Open flames, Sparks, Hot surfaces
P262 - Do not get in eyes, on skin, or on clothing.
P271+P403 - Use and store only outdoors or in a well-ventilated place.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P377 - LEAKING GAS FIRE: Do not extinguish, unless leak can be stopped safely.
P381 - Eliminate all ignition sources if safe to do so.



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

P302, P336, P315 - IF ON SKIN: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.
CGA-PG05 - Use a back flow preventive device in the piping.
CGA-PG12 - Do not open valve until connected to equipment prepared for use.
CGA-PG06 - Close valve after each use and when empty.
CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles.
CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

Other hazards which do not result in classification : Contact with liquid may cause cold burns/frostbite.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%
Ethane (Main constituent)	(CAS-No.) 74-84-0	100

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact : The liquid may cause frostbite. For exposure to liquid, immediately warm frostbite area with warm water not to exceed 105°F (41°C). Water temperature should be tolerable to normal skin. Maintain skin warming for at least 15 minutes or until normal coloring and sensation have returned to the affected area. In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.

First-aid measures after eye contact : The liquid may cause frostbite. Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide, Dry chemical, Water spray or fog.

5.2. Special hazards arising from the substance or mixture

Fire hazard : EXTREMELY FLAMMABLE GAS. If venting or leaking gas catches fire, do not extinguish flames. Flammable vapors may spread from leak, creating an explosive reignition hazard. Vapors can be ignited by pilot lights, other flames, smoking, sparks, heaters, electrical equipment, static discharge, or other ignition sources at locations distant from product handling point. Explosive atmospheres may linger. Before entering an area, especially a confined area, check the atmosphere with an appropriate device.

Explosion hazard : EXTREMELY FLAMMABLE GAS. Forms explosive mixtures with air and oxidizing agents.

Reactivity : No reactivity hazard other than the effects described in sub-sections below.



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

5.3. Advice for firefighters

- Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.
- Protection during firefighting : Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.
- Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Stop flow of product if safe to do so.

Use water spray or fog to knock down fire fumes if possible.

Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
- Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : **Danger: Flammable, liquefied gas.** FORMS EXPLOSIVE MIXTURES WITH AIR. Immediately evacuate all personnel from danger area. Use self-contained breathing apparatus where needed. Remove all sources of ignition if safe to do so. Reduce vapors with fog or fine water spray, taking care not to spread liquid with water. Shut off flow if safe to do so. Ventilate area or move container to a well-ventilated area. Flammable vapors may spread from leak and could explode if reignited by sparks or flames. Explosive atmospheres may linger. Before entering area, especially confined areas, check atmosphere with an appropriate device.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Try to stop release. Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Use only explosion-proof equipment.

Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

All piped systems and associated equipment must be grounded.

Leak-check system with soapy water; never use a flame.

May cause anesthetic effects.

Avoid breathing gas.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store only where temperature will not exceed 125°F (52°C). Post "No Smoking/No Open Flames" signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g. NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethane (74-84-0)	
ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

Appropriate engineering controls

: Use an explosion-proof local exhaust system. Local exhaust and general ventilation must be adequate to meet exposure standards. MECHANICAL (GENERAL): **Inadequate - Use only in a closed system.** Use explosion proof equipment and lighting.

Hand protection

: Wear working gloves when handling gas containers.



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

Eye protection	: Wear safety glasses with side shields. Wear safety glasses with side shields or goggles when transfilling or breaking transfer connections.
Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA). Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
Thermal hazard protection	: Wear cold insulating gloves when transfilling or breaking transfer connections.
Environmental exposure controls	: Refer to local regulations for restriction of emissions to the atmosphere.
Other information	: Consider the use of flame resistant anti-static safety clothing. Wear safety shoes while handling containers.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Gas
Appearance	: Colorless gas.
Molecular mass	: 30 g/mol
Color	: Colorless.
Odor	: Odorless. Stenchant often added.
Odor threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: -183 °C
Freezing point	: No data available
Boiling point	: -88 °C
Flash point	: -135 °C TCC
Critical temperature	: 32.4 °C
Auto-ignition temperature	: 515 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: 3 – 12.5
Vapor pressure	: 3780 kPa
Critical pressure	: 4872 kPa
Relative vapor density at 20 °C	: No data available
Relative density	: 0.54
Density	: 0.506 – 0.583 g/cm ³ (at 15 °C)
Relative gas density	: 1
Solubility	: Water: 61 mg/l
Partition coefficient n-octanol/water (Log Pow)	: 1.81
Partition coefficient n-octanol/water (Log Kow)	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: None.
Explosion limits	: No data available

9.2. Other information

Gas group	: Press. Gas (Liq.)
-----------	---------------------

EN (English US)

SDS ID: P-4592

5/9



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

Additional information : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

May occur.

10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

10.5. Incompatible materials

Oxidizing agents. Chlorine dioxide. Chlorine. Chlorine dioxide and ethane explode spontaneously; chlorine and ethane mixtures have been known to explode.

10.6. Hazardous decomposition products

At high temperature and low pressure, ethane decomposes to form hydrogen. Thermal decomposition may produce : Carbon dioxide. Carbon monoxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethane (1f)74-84-0	
LC50 Inhalation - Rat	658 mg/l/4h
ATE US (vapors)	658 mg/l/4h
ATE US (dust, mist)	658 mg/l/4h

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No ecological damage caused by this product.

12.2. Persistence and degradability

Ethane (74-84-0)	
Persistence and degradability	The substance is biodegradable. Unlikely to persist.

Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

12.3. Bioaccumulative potential

Ethane (74-84-0)	
Partition coefficient n-octanol/water (Log Pow)	1.81
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	Not expected to bioaccumulate due to the low log Kow (log Kow < 4). Refer to section 9.

12.4. Mobility in soil

Ethane (74-84-0)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Effect on ozone layer : None.
Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

SECTION 14: Transport information

In accordance with DOT
Transport document description (DOT) : UN1035 Ethane, 2.1
UN-No.(DOT) : UN1035
Proper Shipping Name (DOT) : Ethane
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Hazard labels (DOT) : 2.1 - Flammable gas



Additional information

Emergency Response Guide (ERG) Number : 115 (UN1035)
Other information : No supplementary information available.
Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1035
Proper Shipping Name (IMDG) : ETHANE
Class (IMDG) : 2 - Gases
Division (IMDG) : 2.1 - Flammable gases
MFAG-No : 115

Air transport

UN-No. (IATA) : 1035



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

Proper Shipping Name (IATA) : Ethane
Class (IATA) : 2
Civil Aeronautics Law : Gases under pressure/Gases flammable under pressure

SECTION 15: Regulatory information

15.1. US Federal regulations

Ethane (74-84-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard Sudden release of pressure hazard Fire hazard
-------------------------------------	---

15.2. International regulations

CANADA

Ethane (74-84-0)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Ethane (74-84-0)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

15.2.2. National regulations

Ethane (74-84-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Ethane(74-84-0)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List



Ethane



Safety Data Sheet P-4592

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.
Issue date: 01/01/1979 Revision date: 04/13/2021 Supersedes: 02/04/2021 Version: 2.0

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.

Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from www.lindeus.com. If you have questions regarding Linde SDSs, would like the document number and date of the latest SDS, or would like the names of the Linde suppliers in your area, phone or write the Linde Call Center (Phone: 1-800-772-9247; Address: Linde Call Center, Linde Inc, P.O. Box 44, Tonawanda, NY 14151-0044).

Linde, Praxair, the Linde wordmark and the Flowing Airstream design are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2020, Linde plc.

Revision date

: 04/13/2021

NFPA health hazard


: 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard

: 4 - Materials that rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and burn readily.

NFPA instability

: 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 4 Severe Hazard
Physical : 3 Serious Hazard

SDS US GHS DUAL BRANDED LINDE->PRAXAIR

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.