



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

SECTION 1: Product and company identification

1.1. Product identifier

Product form : Substance
Substance name : Silicon tetrafluoride
CAS-No. : 7783-61-1
Formula : SiF₄

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use; Use as directed.

1.3. Details of the supplier of the safety data sheet

Linde Inc.
10 Riverview Drive
Danbury, CT 06810-6268, USA
www.lindeus.com

Linde Inc. 1-844-44LINDE (1-844-445-4633)

1.4. Emergency telephone number

Emergency number : Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week
— Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887
(collect calls accepted, Contract 17729)

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

GHS US classification

Press. Gas (Comp.) H280
Acute Tox. 2 (Inhalation: gas) H330
Skin Corr. 1A H314
Eye Dam. 1 H318

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



GHS04

GHS05

GHS06

Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED
H314 - CAUSES SEVERE SKIN BURNS AND EYE DAMAGE
H330 - FATAL IF INHALED
CGA-HG22 - CORROSIVE TO THE RESPIRATORY TRACT

Precautionary statements (GHS US) :

P202 - Do not handle until all safety precautions have been read and understood.
P260 - Do not breathe gas/vapors
P262 - Do not get in eyes, on skin, or on clothing.
P264 - Wash exposed skin thoroughly after handling
P271+P403 - Use and store only outdoors or in a well-ventilated place.
P280+P284 - Wear protective gloves, protective clothing, eye protection, respiratory protection, and/or face protection.
P303, P361, P353, P363, P310 - IF ON SKIN OR (HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Immediately call a poison center or doctor/physician.

EN (English US)

SDS ID: P-4652

1/9



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

CGA-PG34 - SPECIFIC TREATMENT: Immediately apply calcium gluconate or equivalent to affected areas.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P310 - Immediately call a poison center or doctor/physician.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Contact an ophthalmologist immediately.

P405 - Store locked up.

P501 - Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

CGA-PG05 - Use a back flow preventive device in the piping.

CGA-PG20+CGA-PG10 - Use only with equipment of compatible materials of construction and rated for cylinder pressure.

CGA-PG12 - Do not open valve until connected to equipment prepared for use.

CGA-PG18 - When returning cylinder, install leak tight valve outlet cap or plug.

CGA-PG06 - Close valve after each use and when empty.

CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).

2.3. Other hazards

Other hazards which do not result in classification : None.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Name	Product identifier	%
Silicon tetrafluoride (Main constituent)	(CAS-No.) 7783-61-1	100

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : Remove to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Call a physician. . WARNING: To avoid possible chemical burns, the rescuer should avoid breathing any exhaled air from the victim.
- First-aid measures after skin contact : In case of contact, immediately flush affected areas with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician. Wash clothing before reuse. Discard contaminated shoes.
Soak burned areas in ice and, if available, an aqueous solution of 0.2% benzethonium chloride (aka Hyamine 1622 solution) or zephiran chloride (aka bezalkonium chloride solution) Alternatively, Apply calcium gluconate cream to affected areas on the skin.
- First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately.
- First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance. Do not give morphine, barbiturates, or cardiac or respiratory stimulants.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam, dry chemical, carbon dioxide.
- Unsuitable extinguishing media : Water may be ineffective.



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

5.2. Special hazards arising from the substance or mixture

Reactivity : Reacts with water to form hydrogen fluoride fumes.

5.3. Advice for firefighters

Firefighting instructions : **DANGER! Toxic, corrosive, high-pressure gas.**

Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Stop flow of gas if safe to do so, while continuing cooling water spray. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.

Special protective equipment for fire fighters : Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.

Specific methods : Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.

Other information : Containers are equipped with a pressure relief device. (Exceptions may exist where authorized by DOT.).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Reacts with water to form hydrogen fluoride fumes. **Danger: Toxic. Corrosive.** Wear a self-contained breathing apparatus and appropriate personal protective equipment (PPE). (gas tight, chemical-protective) Evacuate personnel to a safe area. Approach suspected leak area with caution. Remove all sources of ignition. Toxic, corrosive vapor can spread from spill. Ventilate area or move container to a well-ventilated area. Before entering the area, especially a confined area, check the atmosphere with an appropriate device.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent waste from contaminating the surrounding environment. Prevent soil and water pollution. Dispose of contents/container in accordance with container supplier/owner instructions.

6.3. Methods and material for containment and cleaning up

No additional information available

6.4. Reference to other sections

See also sections 8 and 13.



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Do not breathe gas/vapor. Avoid all contact with skin, eyes, or clothing. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE: When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Silicon tetrafluoride (7783-61-1)	
ACGIH	Not established
USA OSHA	Not established

8.2. Exposure controls

- Appropriate engineering controls : Use only in a closed system. A corrosion-resistant, forced-draft fume hood is preferred. LOCAL EXHAUST: A corrosion-resistant system is acceptable.
- In semiconductor process gas and other suitable applications, Linde recommends the use of engineering controls such as gas cabinet enclosures, automatic gas panels (used to purge systems on cylinder changeout), excess-flow valves throughout the gas distribution system, double containment for the distribution system, and continuous gas monitors.
- Eye protection : Provide readily accessible eye wash stations and safety showers. Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with OSHA 29 CFR 1910.133.
- Skin and body protection : Wear metatarsal shoes and work gloves for cylinder handling, and protective clothing where needed. Wear appropriate chemical gloves during cylinder changeout or wherever contact with product is possible. Select per OSHA 29 CFR 1910.132, 1910.136, and 1910.138.



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

Respiratory protection : When workplace conditions warrant respirator use, follow a respiratory protection program that meets OSHA 29 CFR 1910.134, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas
Molecular mass : 104 g/mol
Color : Colorless. Gives off white fumes in moist air.
Odor : choking Irritating
Odor threshold : No data available
pH : Not applicable.
Relative evaporation rate (butyl acetate=1) : No data available
Relative evaporation rate (ether=1) : Not applicable.
Melting point : -86.8 °C (-124.24°F)
Freezing point : No data available
Boiling point : -94.8 °C (-138.6°F)
Flash point : Not applicable.
Critical temperature : -14.2 °C 6.44°F)
Auto-ignition temperature : Not applicable.
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : Not applicable.
Critical pressure : 37.1 bar (538.9 psia)
Relative vapor density at 20 °C : No data available
Relative density : Not known.
Density : 4.31 kg/m³ (0.269 lb/ft³) (at 21.1 °C (70 °F))
Relative gas density : 3.6
Solubility : Reacts with water.
Water: No data available
Partition coefficient n-octanol/water (Log Pow) : Not applicable.
Partition coefficient n-octanol/water (Log Kow) : Not applicable.
Viscosity, kinematic : Not applicable.
Viscosity, dynamic : Not applicable.
Explosive properties : Not applicable.
Oxidizing properties : No data available
Explosion limits : Non flammable.

9.2. Other information

Additional information : Gas/vapor heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with water to form hydrogen fluoride fumes.

10.2. Chemical stability

Stable under normal conditions.



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

10.3. Possibility of hazardous reactions

May occur.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

Alkali metals. Water. Sodium. Trimethylamine.

10.6. Hazardous decomposition products

Fluorine. Silicon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Silicon tetrafluoride (lf)7783-61-1	
LC50 Inhalation - Rat [ppm]	922 ppm/1h
ATE US (gases)	461 ppmV/4h

Skin corrosion/irritation : CAUSES SEVERE SKIN BURNS.

pH: Not applicable.

Serious eye damage/irritation : CAUSES SERIOUS EYE DAMAGE.

pH: Not applicable.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : No data available.

12.2. Persistence and degradability

Silicon tetrafluoride (7783-61-1)	
Persistence and degradability	Not applicable for inorganic gases.

12.3. Bioaccumulative potential

Silicon tetrafluoride (7783-61-1)	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No data available.

12.4. Mobility in soil

Silicon tetrafluoride (7783-61-1)	
Mobility in soil	No data available.
Ecology - soil	Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.

Effect on ozone layer : None.



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not attempt to dispose of residual or unused quantities. Return container to supplier.

SECTION 14: Transport information

In accordance with DOT

Transport document description (DOT) : UN1859 Silicon tetrafluoride, 2.3
UN-No.(DOT) : UN1859
Proper Shipping Name (DOT) : Silicon tetrafluoride
Class (DOT) : 2.3 - Class 2.3 - Poisonous gas 49 CFR 173.115
Hazard labels (DOT) : Poison Gas
2.3 - Poison gas
8 - Corrosive substances



DOT Special Provisions (49 CFR 172.102) : 2 - This material is poisonous by inhalation (see 171.8 of this subchapter) in Hazard Zone B (see 173.116(a) or 173.133(a) of this subchapter), and must be described as an inhalation hazard under the provisions of this subchapter.

Additional information

Emergency Response Guide (ERG) Number : 125;173

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:
- Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

Transport by sea

UN-No. (IMDG) : 1859
Proper Shipping Name (IMDG) : SILICON TETRAFLUORIDE
Class (IMDG) : 2 - Gases
Division (IMDG) : 2.3 - Toxic gases
MFAG-No : 125

Air transport

UN-No. (IATA) : 1859
Proper Shipping Name (IATA) : Silicon tetrafluoride
Class (IATA) : 2 - Gases
Civil Aeronautics Law : Gases under pressure/Gases toxic under pressure

SECTION 15: Regulatory information

15.1. US Federal regulations

Silicon tetrafluoride (7783-61-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory.



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

15.2. International regulations

CANADA

Silicon tetrafluoride (7783-61-1)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

Silicon tetrafluoride (7783-61-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

15.2.2. National regulations

Silicon tetrafluoride (7783-61-1)

Listed introduction on Australian Industrial Chemicals Introduction Scheme (AICIS Inventory)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on KECL/KECI (Korean Existing Chemicals Inventory)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on the TCSI (Taiwan Chemical Substance Inventory)

15.3. US State regulations

Silicon tetrafluoride(7783-61-1)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No
State or local regulations	U.S. - New Jersey - Right to Know Hazardous Substance List



Silicon tetrafluoride

Safety Data Sheet P-4652

This SDS conforms to U.S. Code of Federal Regulations 29 CFR 1910.1200, Hazard Communication.

Issue date: 01/01/1980 Revision date: 05/24/2022 Supersedes: 02/09/2021 Version: 1.1

SECTION 16: Other information

Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.

Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from www.lindeus.com. If you have questions regarding Linde SDSs, would like the document number and date of the latest SDS, or would like the names of the Linde suppliers in your area, phone or write the Linde Call Center (Phone: 1-844-44-Linde (1-844-445-4633); Address: Linde Call Center, Linde Inc, P.O. Box 44, Tonawanda, NY 14151-0044).

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2022, Linde Inc.

Revision date

: 05/24/2022

NFPA health hazard

: 3 - Materials that, under emergency conditions, can cause serious or permanent injury.

NFPA fire hazard


: 0 - Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand.

NFPA instability

: 2 - Materials that readily undergo violent chemical change at elevated temperatures and pressures.

NFPA specific hazard

: W - Unusual reactivity with water. This indicates a potential hazard using water to fight a fire involving this material.



SDS US (GHS HazCom 2012) - Linde 2022

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.