



UpTime[®] Sub-Atmospheric Delivery System

A safe, cost-effective dopant gas delivery system for ion implanters



Increase productivity with the UpTime[®] delivery system - OEM qualified and production proven

The UpTime[®] sub-atmospheric dopant gas delivery system is designed as an alternative to existing adsorbent-based technology used in ion implanters. Compared to the existing technology, the UpTime system offers industry leading product capacity, higher product purity and a lower cost of ownership.

The UpTime system is comprised of an internal vacuum actuated valve in series with a specially designed internal flow restrictor. The UpTime device is designed for safety, with two different types of safeguards: a mechanical actuator and a flow restrictor.

UpTime Product Family


- Enriched ⁷²Germanium Tetrafluoride
- Germanium Tetrafluoride
- Silicon Tetrafluoride
- Arsine
- Phosphine
- Isotopically Enriched ¹¹Boron Trifluoride.*

US Patent Numbers: 5,937,895; 6,007,609

*Additional ultra-high purity gases are available upon request

Features

- Sub-atmospheric delivery
- Internal flow restrictor limits flow to 20 sccm
- SEMI[®] S2 and S8 compliant
- Highest equivalent-cylinder product capacity
- High product utilization
- Robust safety features
- Ultra-high purity gas



UpTime[®] Sub-Atmospheric Delivery System

A safe, cost-effective dopant gas delivery system for ion implanters

Enabling next-generation technology

Praxair specializes in developing high performance and cost-effective products to serve next-generation semiconductor manufacturing.

About Praxair

Praxair is dedicated to helping semiconductor manufacturers lower costs, improve productivity, enhance technology and reduce environmental impact by serving as a single, integrated source for a variety of process gases, materials, and related equipment and services.

Praxair's commitment to materials science and gas technology includes:

Process Consumables

- Ultra-high purity semiconductor process gases
- Sputtering targets
- ALD/CVD precursors

Fab Infrastructure and Services

- Bulk and on-site gas production
- Analytical systems and services
- Process gas delivery systems
- Total gas and chemical management services
- Integrated supply chain management services

Silicon Tetrafluoride (SiF₄) Specification, 4.0 grade

- Fill pressure 600 psig
- Internal flow restrictor limits flow to 118 sccm

Component	Value (ppm)
Argon + Oxygen	50
Carbon Dioxide	25
Nitrogen	25

Shelf life: 24 months

Gas Stick Recommendations

- 1/4" FVCR cylinder connection
- Vacuum required at cylinder connection between 100 and 610 torr
- Low pressure transducer (ideally 0-1000 torr range)
- Vacuum pressure mass flow controller
- Normally closed pneumatic isolation valve suitable for ≥ 600 psig service that automatically closes if pressure exceeds working pressure of low-pressure components
- All components not protected by an isolation valve are suitable for ≥ 600 psig service

Gas Box Recommendations

- Toxic gas monitoring of the gas box exhaust
- Gas box exhaust interlocked and abated



Cylinder Specification

Cylinder Size	Overall Height A	Height to Connection B	Cylinder Body Height C	Diameter D	Content Fill Weight
UT-SSELB	16.7" 423mm	13.9" 354mm	11.9" 301mm	2.0" 51mm	100g
UT-5	18.0" 457mm	15.3" 389mm	13.25" 366mm	4.4" 111mm	575g
UT-6	22.5" 571mm	19.7" 500mm	17.5" 445mm	6.25" 159mm	1200g



© Copyright 2012 Praxair Technology, Inc. All rights reserved
Praxair, the Flowing Airstream design, *Making our planet more productive*, are trademarks or registered trademarks of Praxair Technology, Inc. in the United States and/or other countries. Other trademarks used herein are the registered trademarks of their respective owners.

The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

P-8894 C-5 6/12

Praxair, Inc.
39 Old Ridgebury Road
Danbury, CT 06810-5113
USA

www.praxair.com
info@praxair.com

Telephone:
Praxair Electronics
USA
(TEL) 1-800-446-8765 (FAX) 1-800-447-5040
Europe
(TEL) 32 14 250 611 (FAX) 32 14 581 505
Asia
(TEL) 886 3 554 3538 (FAX) 886 3 554 3539